

**OML50 - LED ARRAY D TW
CORNER R2925 45° 950 DIM5**

31094 9005

[Bekijk op website](#)**Algemene info**

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	@ 2700K: LED cluster 52,1W / CRI>90 (R9: 50) / 2700K-5000K / 6832lm Or @ 5000K: LED cluster 47,3W / CRI>90 (R9: 50) / 2700K-5000K / 8176lm
SMDC	SDCM3
RISK-GROEP	RG1
LED TECHNIEK (LICHTBRON)	@ 2700K: 6832lm // 52,1W // 131lm/W Or @ 5000K: 8176lm // 47,3W // 173lm/W

Opties

WIRELESS CONTROL DIM5

Notes: