
DELTALIGHT




FRAX MB POLE 92714 DIM5

REFERENCE 26020 9215 N

AVAILABLE IN
ANTHRACITE 26020 9215 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	9 x LENS SP-14° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC INCL.1 x CABLE H05 RN-F 5 x 1mm² 6m

Electrical info	
ELECTRICAL	110-277V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 23,4W / CRI>90 (R9: 50) / 2700K / 2423lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	14°
LED TECHNICS (LIGHT SOURCE)	2423lm // 23,4W // 103lm/W
LED TECHNICS (LUMINAIRE)	1890lm // 26,9W // 70lm/W

Requirements

FRAX BRACKET

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP

DELTALIGHT


FRAX MB POLE 92714 DIM5

26020 9215 N

For detailed installation instructions, please consult the manual : **26020_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

Light altering devices




26070 0020 N FRAX M KAP N ☐


Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS ☐



26071 0050 N FRAX POLE 60 BRACKET N ☐



26071 0060 N FRAX POLE 80 BRACKET N ☐

Notes: