



DEEP RINGO SOFT 93045

19437 9030 BRA

AVAILABLE IN

NOIR 19437 9030 B

ALU BROSSÉ 19437 9030 BRA

ANTHRACITE BROSSÉ 19437 9030 BRAT

BRONZE BRUN BROSSÉ 19437 9030 BRBB

CUIVRE BROSSÉ 19437 9030 BRCU

OR BROSSÉ 19437 9030 BRG

BRONZE VIEUX BROSSÉ 19437 9030 BROB

CRÈME 19437 9030 CR


FLEMISH BRONZE 19437 9030 FBR

FLEMISH GOLD 19437 9030 FG

COULEUR OR 19437 9030 GC

NOIR PIANO 19437 9030 PB

BLANC 19437 9030 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR WFL-45° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	814lm // 11,7W // 69lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

For detailed installation instructions, please consult the manual : [19437_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

les batteries de secours

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

DELTALIGHT

DEEP RINGO SOFT 93045

19437 9030 BRA


les alimentations led

of Fixtures



web2print_power_supply_info_box

Min current | Max current




300 48 500 ED1

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1

2

Dimtype: 1 à 10 V

Cutout dimension (mm): 30




300 48 500 ED5

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2

Dimtype: DALI

Cutout dimension (mm): 45




300 48 500 MDL

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL

2

Dimtype: non dimmable

Cutout dimension (mm): 30




300 48 500 WDL

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL

2

Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45




300 90 61

LED POWER SUPPLY MULTI-POWER DIM6

2

Dimtype: fin de phase ou bouton poussoir

Cutout dimension (mm): 56




300 90 63

LED POWER SUPPLY MULTI-POWER DIM9

3(3)

Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 82




300 90 64

LED POWER SUPPLY MULTI-POWER DIM7

2(1)

Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 72




300 90 68

LED POWER SUPPLY MULTI-POWER DIM5

2(1)

Dimtype: DALI

Cutout dimension (mm): 72



300 90 69

LED POWER SUPPLY MULTI-POWER HV DIM9









5(3)

Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 84

DEEP RINGO SOFT 93045

19437 9030 BRA

	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1 à 10 V ou bouton poussoir Cutout dimension (mm): 55	1(1) ☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	1(1) ☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	2 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	2 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	2 ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	3(3) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	2 ☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 ☐

DEEP RINGO SOFT 93045

19437 9030 BRA

	<u>21032 0305</u> Dimtype: DALI Cutout dimension (mm): 30	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2 ☐
--	---	---	-----------------------------------

Notes: