

DELTALIGHT




INLET TRIMLESS H7 927

REFERENCE 13213 9200 B-W

AVAILABLE IN
BLACK-WHITE 13213 9200 B-W
GOLD COLORED-WHITE 13213 9200 GC-W
WHITE-WHITE 13213 9200 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Wall Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	50
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 24V-DC

Electrical info	
ELECTRICAL	24V-DC
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LEDFLEX 0,9W / CRI>90 / 2700K /109lm
LED TECHNICS (LIGHT SOURCE)	109lm // 0,9W //121lm/W
LED TECHNICS (LUMINAIRE)	44lm // 1W // 42lm/W

Requirements

MOUNTING KIT INLET TRIMLESS H7
LED POWER SUPPLY 24V-DC (Remote)

For detailed installation instructions, please consult the manual : **13213_XXX0_HAND.pdf**

DELTALIGHT


INLET TRIMLESS H7 927

13213 9200 B-W

FINISH YOUR SPECIFICATION

LED power supplies	# of Fixtures
	Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 24 150 LED POWER SUPPLY 24V-DC / 150W — 151 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 75



21012 0101 LED POWER SUPPLY 24V-DC / 60W IP67 DIM1 — 60 ☐

Dimtype: 1-10V


Cutout dimension (mm): 65



21012 0111 LED POWER SUPPLY 24V-DC / 90W IP67 DIM1 — 90 ☐

Dimtype: 1-10V


Cutout dimension (mm): 75



21012 0121 LED POWER SUPPLY 24V-DC / 120W IP67 DIM1 — 121 ☐

Dimtype: 1-10V


Cutout dimension (mm): 75



21012 0135 LED POWER SUPPLY 24V-DC / 60W IP67 DIM5 — 60 ☐

Dimtype: DALI


Cutout dimension (mm): 65



21012 0145 LED POWER SUPPLY 24V-DC / 90W IP67 DIM5 — 90 ☐

Dimtype: DALI


Cutout dimension (mm): 75



21012 0155 LED POWER SUPPLY 24V-DC / 120W IP67 DIM5 — 121 ☐

Dimtype: DALI

Cutout dimension (mm): 75



21012 0160 LED POWER SUPPLY 24V-DC / 24W — 24 ☐


Dimtype: non-dimmable

Cutout dimension (mm): 55

DELTALIGHT

INLET TRIMLESS H7 927


13213 9200 B-W



21012 0171 LED POWER SUPPLY 24V-DC / 60W DIM1 60

Dimtype: 1-10V


Cutout dimension (mm): 61



21012 0181 LED POWER SUPPLY 24V-DC / 90W DIM1 90

Dimtype: 1-10V


Cutout dimension (mm): 70



21012 0191 LED POWER SUPPLY 24V-DC / 120W DIM1 121

Dimtype: 1-10V


Cutout dimension (mm): 70



21012 0205 LED POWER SUPPLY 24V-DC / 60W DIM5 60

Dimtype: DALI

Cutout dimension (mm): 61



21012 0225 LED POWER SUPPLY 24V-DC / 100W DIM5 101

Dimtype: DALI

Cutout dimension (mm): 70

Mounting kits



13210 0030 MOUNTING KIT INLET TRIMLESS H7

Cutout dimension (mm): 80 x 110

Notes: