
DELTALIGHT




SUPERLOOP SLIM OUT 120 SBL 930

REFERENCE 20578 9300 W

AVAILABLE IN
BLACK 20578 9300 B
FLEMISH BRONZE 20578 9300 FBR
FLEMISH GOLD 20578 9300 FG
GOLD COLOURED 20578 9300 GC
WHITE 20578 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 3000K / 5022-6665lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	6665lm // 50,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	2951lm // 57,8W // 51lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM
SUPERLOOP POWERBOX H 900mA
SUPERLOOP POWERBOX H 1200mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT


SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 W

For detailed installation instructions, please consult the manual : **20578_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐



203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐


203 99 56 W CABLE BASE S W ☐

Power box

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B 1 ☐

Dimtype: 1-10V

321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W 1 ☐




20548 0015 B SUPERLOOP POWERBOX H9 900mA DIM5 B 1 ☐

Dimtype: DALI

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 W




	20548 0015 W	SUPERLOOP POWERBOX H9 900mA DIM5 W	1
	**20548 0025 B** **Dimtype: DALI**	SUPERLOOP POWERBOX H9 1200mA DIM5 B	1
	20548 0025 W	SUPERLOOP POWERBOX H9 1200mA DIM5 W	1

LED power supplies


of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current






	**300 90 129** **Dimtype: DALI** **Cutout dimension (mm): 84**	LED POWER SUPPLY 900mA-DC / 60W DIM5	1
	**300 90 130** **Dimtype: DALI** **Cutout dimension (mm): 95**	LED POWER SUPPLY 1200mA-DC / 60W DIM5	1
	**300 90 132** **Dimtype: 1-10V** **Cutout dimension (mm): 80**	LED POWER SUPPLY 1200mA-DC / 70W DIM1	1

Coversets

	**204 00 62 ANO**	COVERSET R 62 ANO	
	204 00 62 B	COVERSET R 62 B	
	204 00 62 W	COVERSET R 62 W	

SUPERLOOP SLIM OUT 120 SBL 930

20578 9300 W


	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B
	204 80 80 W	COVERSET S 80 W
	**204 90 90 ANO**	COVERSET S 90 ANO
	204 90 90 B	COVERSET S 90 B
	204 90 90 W	COVERSET S 90 W

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 930


20578 9300 W

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B ☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W ☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: