
DELTALIGHT




SUPERNOVA LINE 95 DOWN-UP 930 DIM5

REFERENCE 20618 9305 B

AVAILABLE IN
BLACK 20618 9305 B
WHITE 20618 9305 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	13
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY CABLING 2 CIRCUITS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 3 x 0.75mm² + 1 x CABLE 2 x 0.75mm²

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 147W / CRI>90 (R9: 50) / 3000K / 21588lm UP: 4 x (LED cluster 7,4W / CRI>90 (R9: 50) / 3000K / 1079lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 21588lm // 147W // 147lm/W UP: 4316lm // 29,6W // 147lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 15876lm // 169W // 94lm/W UP: 3772lm // 34W // 111lm/W

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS
WIRELESS CONTROL DIM5


SUPERNOVA LINE 95 DOWN-UP 930 DIM5

20618 9305 B

For detailed installation instructions, please consult the manual : **20618 _XXX5_HAND.pdf** , **20618_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Miscellaneous control equipment




300 90 004 ED5 WIRELESS CONTROL DIM5 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45

Coversets








204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐

DELTALIGHT

SUPERNOVA LINE 95 DOWN-UP 930 DIM5

20618 9305 B


	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B
	204 80 80 W	COVERSET S 80 W
	**204 90 90 ANO**	COVERSET S 90 ANO
	204 90 90 B	COVERSET S 90 B

SUPERNOVA LINE 95 DOWN-UP 930 DIM5

20618 9305 B


204 90 90 W COVERSET S 90 W ☐

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)




15225 0340 B SUSPENSION ST B ☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W ☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A. ☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B ☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W ☐

Notes: