



OML50 - PRISMATIC LENS D TW  
984mm 950 DIM5

31626 9005 B

AVAILABLE IN  
BLACK 31626 9005 B

 [View on website](#)



|                             |                                                                                                                                                |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| General info                |                                                                                                                                                |
| LOCATION                    | indoor                                                                                                                                         |
| INGRESS PROTECTION          | IP20                                                                                                                                           |
| WEIGHT (KG)                 | 1.3                                                                                                                                            |
| INFORMATION                 | INCL.DIMMABLE LED POWER SUPPLY (DALI DT8)<br>CABLING 1 CIRCUIT                                                                                 |
| Electrical info             |                                                                                                                                                |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                                           |
| CLASS                       | I                                                                                                                                              |
| POWER SUPPLY                | YES                                                                                                                                            |
| DIM TYPE                    | DALI                                                                                                                                           |
| ENERGY CLASS                | E                                                                                                                                              |
| CERTIFICATES                | EPD, RCM                                                                                                                                       |
| Lightsource info            |                                                                                                                                                |
| LIGHTSOURCE NAME            | LED                                                                                                                                            |
| LIGHTSOURCE                 | @ 2700K: LED cluster 18W / CRI>90 (R9: 50) / 2700K-5000K / 2407lm<br>Or<br>@ 5000K: LED cluster 16,5W / CRI>90 (R9: 50) / 2700K-5000K / 2869lm |
| SDCM                        | SDCM3                                                                                                                                          |
| RISKGROUP                   | RG1                                                                                                                                            |
| LM80                        | L80 > 60000                                                                                                                                    |
| LED TECHNICS (LIGHT SOURCE) | @ 2700K: 2407lm // 18W // 134lm/W<br>Or<br>@ 5000K: 2869lm // 16,5W // 174lm/W                                                                 |

|                       |
|-----------------------|
| Options               |
| WIRELESS CONTROL DIM5 |

Notes: