




LASS-OH! R65 - 3 92734

24821 9220 B

AVAILABLE IN
BLACK 24821 9220 B
GOLD COLOURED 24821 9220 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.3 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	34°
LED TECHNICS (LIGHT SOURCE)	1995lm // 18,3W // 109lm/W
LED TECHNICS (LUMINAIRE)	1577lm // 21W // 75lm/W

Requirements

LASS-OH! POWERBOX
 LED POWER SUPPLY 1050mA-DC DIM

Options

CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90
 CONNECTION ST / CONNECTION TRIMLESS
 SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [24821_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	1 ☐

DELTALIGHT

LASS-OH! R65 - 3 92734



24821 9220 B

	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 54			

Power box	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current

	24814 0075 B LASS-OH! POWERBOX H15 DIM5 B	1	☐
Dimtype: DALI			
	24814 0080 B LASS-OH! POWERBOX H15 B	1	☐
Dimtype: non-dimmable			





Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐
	204 00 90 B COVERSET R 90 B	☐
	204 00 90 W COVERSET R 90 W	☐


DELTALIGHT

LASS-OH! R65 - 3 92734

24821 9220 B

	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐


Suspension parts

	<u>328 10 01</u> SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		

DELTALIGHT

LASS-OH! R65 - 3 92734

24821 9220 B



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: