





POLESANO W 94043

15931 9420 N-B

AVAILABLE IN
ALU GREY-BLACK 15931 9420 A-B
ANTHRACITE-BLACK 15931 9420 N-B



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP66
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	5.4
ADJUSTABILITY	0° to 55° swiveling, 355° rotatable
INFORMATION	16 x LENS FL-47° INCLLED POWER SUPPLY 900mA-DC $\lambda > 0,9$ Inrush current : 32A - 355µs @ 230V-AC Max. 10 units on circuit breaker B 16A @ 230V-AC (13 units on B 20A)
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, ENEC+, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 41,6W / CRI>90 (R9: 62) / 4000K / 5136lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	47°
LED TECHNICS (LIGHT SOURCE)	5136lm // 41,6W // 123lm/W
LED TECHNICS (LUMINAIRE)	3699lm // 47,8W // 77lm/W

Remarks

[Take a look at the POLESANO brochure](#)

Options

POLESANO FLOOR BASE

Accessories

HONEYCOMB S105

LINEAR SPREAD LENS S105

DELTALIGHT


POLESANO W 94043

15931 9420 N-B


For detailed installation instructions, please consult the manual : [15931_XXXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Light altering devices




431 03 01 B HONEYCOMB S105 B

☐

431 03 02 LINEAR SPREAD LENS S105

☐

Other



15932 0010 N POLESANO FLOOR BASE N

☐

Notes: