
DELTALIGHT




M20/M26H - SPY 391 93040 DIM5

REFERENCE 23316 9335 PB

AVAILABLE IN
BLACK 23316 9335 B
BRUSHED ALU 23316 9335 BRA
BRUSHED ANTHRACITE 23316 9335 BRAT
BRUSHED COPPER 23316 9335 BRCU
BRUSHED GOLD 23316 9335 BRG
BRUSHED OLD BRONZE 23316 9335 BROB
FLEMISH BRONZE 23316 9335 FBR
FLEMISH GOLD 23316 9335 FG
GOLD COLOURED 23316 9335 GC
PIANO BLACK 23316 9335 PB
WHITE 23316 9335 W







View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	883lm // 9,9W // 89lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 39 TUBE or VISOR 39
LED POWER SUPPLY 48V-DC

DELTALIGHT

M20/M26H - SPY 391 93040 DIM5

23316 9335 PB

For detailed installation instructions, please consult the manual : **23316_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices




24144 0030 B VISOR 39 B

DELTALIGHT



M20/M26H - SPY 391 93040 DIM5

23316 9335 PB

Finish your product

	**24144 0010 B**	SPY 39 TUBE B	☐
	24144 0010 FBR	SPY 39 TUBE FBR	☐
	24144 0010 FG	SPY 39 TUBE FG	☐
	24144 0010 GC	SPY 39 TUBE GC	☐
	24144 0010 W	SPY 39 TUBE W	☐
	**24144 0070**	SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26H + SBL		Available Colours
	**30411 9205** SHIFTLINE M26H + SBL 2m DIM5	● ○
	**30411 9305** SHIFTLINE M26H + SBL 2m DIM5	● ○
	**30412 9205** SHIFTLINE M26H + SBL 3m DIM5	● ○
	**30412 9305** SHIFTLINE M26H + SBL 3m DIM5	● ○


DELTALIGHT

M20/M26H - SPY 391 93040 DIM5

23316 9335 PB




30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5

SHIFTLINE M26H profile


Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile

Available Colours



23397 0000 SPM20 ST - PROFILE



23397 0020 SPM20 ST - PROFILE 2m







23397 0030 SPM20 ST - PROFILE 3m

DELTALIGHT

M20/M26H - SPY 391 93040 DIM5

23316 9335 PB

SPLITLINE M20 profile	Available Colours
 **420 20 10 00** SPM20 - PROFILE 1m	
 **420 20 20 00** SPM20 - PROFILE 2m	
 **420 20 30 00** SPM20 - PROFILE 3m	
 **23301 0000** SPM20 - PROFILE B	

Notes: