



ENTERO SQ-M TRIMLESS TW 94045



28567 9030 B

AVAILABLE IN

BLACK 28567 9030 B

FULL WHITE 28567 9030 FW

GOLD COLOURED 28567 9030 GC



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.405
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 30° available
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	979lm // 9W // 109lm/W
LED TECHNICS (LUMINAIRE)	738lm // 10,4W // 71lm/W

Requirements

MOUNTING KIT ENTERO SQUARE M

LED POWER SUPPLY 500mA-DC TW (Remote)

Accessories

ENTERO M HONEYCOMB

ENTERO M LINEAR SPREAD LENS

ENTERO M SPREAD LENS

ENTERO M SOFTENING LENS

ENTERO M GLASS SBL

ENTERO SQ-M TRIMLESS TW 94045


28567 9030 B

For detailed installation instructions, please consult the manual : [28567_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Plasterboard	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Stucanet	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Wood	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Concrete + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Lintel + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Hollow-core slab + plaster	 28400 0050 - MOUNTING KIT ENTERO SQ-M	Required
 Stretched ceiling	 28400 0170 - MOUNTING KIT ENTERO SQ-M WSC	Required
	 28400 0110 - MOUNTING KIT ENTERO SQ-M CSC	Required

FINISH YOUR SPECIFICATION


LED power supplies	# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current Max current
 21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 Dimtype: DALI Cutout dimension (mm): 85	2

DELTALIGHT

ENTERO SQ-M TRIMLESS TW 94045

28567 9030 B

Mounting kits




28400 0050 MOUNTING KIT ENTERO SQ-M

Cutout dimension (mm): 122 x 122

☐

Mounting kits stretched ceiling



28400 0110 MOUNTING KIT ENTERO SQ-M CSC


☐



28400 0170 MOUNTING KIT ENTERO SQ-M WSC


☐

Light altering devices




28500 0070 ENTERO M LINEAR SPREAD LENS

☐




28500 0080 ENTERO M SPREAD LENS

☐




28500 0090 ENTERO M SOFTENING LENS

☐



28500 0100 ENTERO M GLASS SBL

☐




28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

☐

DELTALIGHT

ENTERO SQ-M TRIMLESS TW 94045

28567 9030 B

	28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B	☐
--	---	--------------------------

Replaceable reflector / lens

	24611 0220 SPY 66 REFLECTOR 18°	☐
---	--	--------------------------

	24611 0230 SPY 66 REFLECTOR 30°	☐
---	--	--------------------------

	24611 0240 SPY 66 REFLECTOR 45°	☐
---	--	--------------------------

Notes: