



## SUPERLOOP SLIM IN 170 SBL 930

20575 9300 FG

AVAILABLE IN



**BLACK** 20575 9300 B

**FLEMISH BRONZE** 20575 9300 FBR

**FLEMISH GOLD** 20575 9300 FG

**GOLD COLOURED** 20575 9300 GC

**WHITE** 20575 9300 W



[View on website](#)



### General info

|                           |  |
|---------------------------|--|
| <b>LOCATION</b>           | indoor   |
| <b>INSTALLATION</b>       | Ceiling Suspended  |
| <b>INGRESS PROTECTION</b> | IP20   |
| <b>WEIGHT (KG)</b>        | 3.4  |
| <b>ADJUSTABILITY</b>      | non adjustable   |
| <b>INFORMATION</b>        | INCL.PC SBL<br>EXCL.LED POWER SUPPLY 1200-1700mA-DC<br>INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m<br>INCL.1 x CABLE 2 x 0.75mm <sup>2</sup> |

### Electrical info

|                     |                           |
|---------------------|---------------------------|
| <b>CLASS</b>        | III                       |
| <b>DIM TYPE</b>     | depending on power supply |
| <b>ENERGY CLASS</b> | E                         |
| <b>CERTIFICATES</b> | CB, ENEC, EPD             |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED cluster 51,7-71,4W / CRI>90 (R9: 59) / 3000K / 7128-9460lm |
| <b>SDCM</b>                        | SDCM3  |
| <b>LM80</b>                        | L70 > 30000  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 9460lm // 71,4W // 132lm/W                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4188lm // 82,1W // 51lm/W                                      |

### Requirements

LED POWER SUPPLY 1200 / 1700mA-DC DIM  
SUPERLOOP POWERBOX H 1200mA  
SUPERLOOP POWERBOX H 1700mA

### Options

CABLE BASE R / S  
COVERSET R 62-90-100 / S 62-80-90  
CONNECTION ST / CONNECTION TRIMLESS  
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20575\\_XXX0\\_HAND.pdf](#)


# DELTALIGHT

## SUPERLOOP SLIM IN 170 SBL 930

20575 9300 FG

### FINISH YOUR SPECIFICATION

#### Current supply



**203 99 55 ANO** CABLE BASE R ANO

**203 99 55 B** CABLE BASE R B

**203 99 55 W** CABLE BASE R W



**203 99 56 ANO** CABLE BASE S ANO

**203 99 56 B** CABLE BASE S B

**203 99 56 W** CABLE BASE S W


#### Power box

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**321 55 312 ED1 B** SUPERLOOP POWERBOX H8 1200mA DIM1 B

1

Dimtype: 1-10V

**321 55 312 ED1 W** SUPERLOOP POWERBOX H8 1200mA DIM1 W

1



**321 55 317 ED1 B** SUPERLOOP POWERBOX H8 1700mA DIM1 B

1

Dimtype: 1-10V


**321 55 317 ED1 W** SUPERLOOP POWERBOX H8 1700mA DIM1 W

1

# DELTALIGHT

## SUPERLOOP SLIM IN 170 SBL 930

20575 9300 FG



**20548 0025 B** SUPERLOOP POWERBOX H9 1200mA DIM5 B

1

Dimtype: DALI

**20548 0025 W** SUPERLOOP POWERBOX H9 1200mA DIM5 W

1


### LED power supplies

### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 90 130** LED POWER SUPPLY 1200mA-DC / 60W DIM5

1

Dimtype: DALI

Cutout dimension (mm): 95




**300 90 132** LED POWER SUPPLY 1200mA-DC / 70W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 80




**300 90 133** LED POWER SUPPLY 1700mA-DC / 99W DIM1

1

Dimtype: 1-10V

Cutout dimension (mm): 80




**21012 0475** LED POWER SUPPLY 1700mA-DC / 92W DIM5

1

Dimtype: DALI

### Coversets



**204 00 62 ANO** COVERSET R 62 ANO


**204 00 62 B** COVERSET R 62 B

**204 00 62 W** COVERSET R 62 W

# DELTALIGHT

## SUPERLOOP SLIM IN 170 SBL 930


20575 9300 FG



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B


**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B


**204 00 100 W** COVERSET R 100 W



**204 62 62 ANO** COVERSET S 62 ANO

**204 62 62 B** COVERSET S 62 B


**204 62 62 W** COVERSET S 62 W



**204 80 80 ANO** COVERSET S 80 ANO

**204 80 80 B** COVERSET S 80 B

**204 80 80 W** COVERSET S 80 W



**204 90 90 ANO** COVERSET S 90 ANO

**204 90 90 B** COVERSET S 90 B

**204 90 90 W** COVERSET S 90 W

# DELTALIGHT

## SUPERLOOP SLIM IN 170 SBL 930

20575 9300 FG

### Suspension parts

---



**328 10 01** SUSPENSION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0340 B** SUSPENSION ST B


Cutout dimension (mm): 27

---

**15225 0340 W** SUSPENSION ST W

### Electric connection parts

---



**328 10 03** CONNECTION TRIMLESS O.F.A.

Cutout dimension (mm): 62 (CONCRETE: 102)

---



**15225 0360 B** CONNECTION ST B

Cutout dimension (mm): 43

---

**15225 0360 W** CONNECTION ST W

Notes: