
DELTALIGHT




# COMPO S HP SOFT 93041

**REFERENCE** 9 15720 9030 C

AVAILABLE IN
**BLACK** 9 15720 9030 B
**CHROMED** 9 15720 9030 C
**DARK CHROMED** 9 15720 9030 DC
**WHITE** 9 15720 9030 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 120 |
| **RECESSED DEPTH (MM)** | 114 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | max.25 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.164 |
| **ADJUSTABILITY** | 0° to 30° swiveling, 355° rotatable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | G |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 8,7W / CRI>90 (R9: 50) / 3000K-1800K / 734lm |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 40° |
| **LED TECHNICS (LIGHT SOURCE)** | 734lm // 8,7W // 99lm/W |
| **LED TECHNICS (LUMINAIRE)** | 492lm // 10W // 49lm/W |

**Requirements**

LED POWER SUPPLY 350 mA - DC

**Accessories**

COMPO S HONEYCOMB SINGLE USE B
COMPO S LINEAR SPREAD LENS
COMPO S SPREAD LENS
COMPO S SOFTENING LENS
COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : **9_15720_XXX0_HAND.pdf**

DELTALIGHT

# COMPO S HP SOFT 93041

9 15720 9030 C

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  System ceiling | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  Plasterboard | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  Wood | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |

## FINISH YOUR SPECIFICATION

### LED Power supply

### # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**

| | | |
|---|---|---|
| **15710 3800** | LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA | 1 |
| **15710 4500** | LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA | 1 |
| **15710 5100** | LED POWER SUPPLY MULTIPOWER 8W DALI DT6 350mA | 1 |

**Dimtype: DALI**

| | | |
|---|---|---|
| **15710 6100** | LED POWER SUPPLY MULTIPOWER 10W DIM8 250mA | 1 |
| **15710 6200** | LED POWER SUPPLY MULTIPOWER 12W DIM1 250mA | 1 |
| **15710 6300** | LED POWER SUPPLY MULTIPOWER 12W DALI DT6 250mA | 1 |

### Mounting kits




**15710 0010 B** MOUNTING KIT COMPO S TRIM B

**Cutout dimension (mm): 55**

**15710 0010 W** MOUNTING KIT COMPO S TRIM W

DELTALIGHT

# COMPO S HP SOFT 93041

9 15720 9030 C




**15710 0040** MOUNTING KIT COMPO S TRIMLESS

**Cutout dimension (mm): 55**

## Light altering devices

**15710 0100 B** COMPO S HONEYCOMB SINGLE USE B

**15710 0110** COMPO S LINEAR SPREAD LENS

**Cutout dimension (mm): 26,5**

**15710 0120** COMPO S SPREAD LENS

**Cutout dimension (mm): 26,5**

**15710 0130** COMPO S SOFTENING LENS

**Cutout dimension (mm): 26,5**

**15710 0140** COMPO S GLASS SBL

**Cutout dimension (mm): 26,5**

Notes: