





SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930 DIM1

20613 9301 B

AVAILABLE IN
BLACK 20613 9301 B
WHITE 20613 9301 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC PRISMATIC INCL.DIMMABLE LED POWER SUPPLY 930mA (DOWN) / 500mA (UP)
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	1-10V
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 930mA: LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 930mA: 5360lm // 37,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 930mA: 3934lm // 43W // 91lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

Requirements

SUSPENSION SET 25 DIM 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930 DIM1

20613 9301 B



For detailed installation instructions, please consult the manual : [20613_XXX1_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐
	204 00 90 ANO COVERSET R 90 ANO	☐

DELTA LIGHT

SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930 DIM1

20613 9301 B



	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTA LIGHT

SUPERNOVA FLAT 65 PRISMATIC DOWN-UP 930 DIM1

20613 9301 B

Suspension parts

	274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B	☐
	274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W	☐
	328 25 43 ED SUSPENSION SET 25 DIM 3m	☐
	328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B	☐
	328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W	☐

Electric connection parts

	15225 0360 B CONNECTION ST B	☐
	15225 0360 W CONNECTION ST W	☐

Notes: