
DELTALIGHT




# LOGIC LINEAR 440 92740

**REFERENCE** 30811 9230 N

AVAILABLE IN
**ANTHRACITE** 30811 9230 N




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - BOX |
| **RECESSED DEPTH (MM)** | 140 |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK09 |
| **WEIGHT (KG)** | 2 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 8 x LENS WFL-40°<br>INCL.LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m<br>INCL.IP68 CONNECTOR 3P<br>ESG 8mm max.500kg |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 0\|50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | non-dimmable |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | CB, ENEC, EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 14,4W / CRI>90 (R9: 55) / 2700K / 1644lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 40° |
| **LED TECHNICS (LIGHT SOURCE)** | 1644lm // 14,4W // 111lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1097lm // 17W // 66lm/W |

**Requirements**

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : **30811_XXX0_HAND.pdf**

DELTALIGHT

# LOGIC LINEAR 440 92740

30811 9230 N

## FINISH YOUR SPECIFICATION


### Ground mounting boxes





**30810 0010** LOGIC LINEAR 440 BOX ☐

**Cutout dimension (mm): 480 x 150**

### Waterproof connection parts




**431 99 02** IP68 JUNCTION BOX 4P ☐




**21034 0150** IP68 Y-CONNECTOR 5P ☐

Notes: