



INFORM SQ P392-6 DOWN-UP 93067

25571 9320 B-B


AVAILABLE IN

BLACK-BLACK 25571 9320 B-B

BLACK-FLEMISH GOLD 25571 9320 B-FG

WHITE-BLACK 25571 9320 W-B

WHITE-WHITE 25571 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.7
ADJUSTABILITY	non adjustable
INFORMATION	72 x REFLECTOR FL-67° (DOWN) EXCL.LED POWER SUPPLY 600mA-DC (DOWN) - 1000mA (UP) INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 4 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: 2 x (LED cluster 10,5W / CRI>90 (R9: 50) / 3000K / 1602lm) UP: 4 x (LED cluster 9,1W / CRI>90 (R9: 50) / 3000K / 1310lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 3204lm // 21W // 152lm/W UP: 5240lm // 36,4W // 145lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2717lm // 24,2W // 113lm/W UP: 3532lm // 41,9W // 84lm/W

Requirements

INFORM POWER SUPPLY 60W

INFORM SQ POWERBOX L 75W

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90


CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [25571_XXX0_HAND.pdf](#)



FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐



LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current	
	25510 0385 INFORM POWER SUPPLY 45W DIM5	only UP or only DOWN	☐
	Dimtype: DALI		
	25510 0405 INFORM POWER SUPPLY 60W DIM5	1	☐
	Dimtype: DALI		

INFORM SQ P392-6 DOWN-UP 93067

25571 9320 B-B



	25510 0430 INFORM POWER SUPPLY 45W	only UP or only DOWN ☐
Dimtype: non-dimmable		
	25510 0450 INFORM POWER SUPPLY 60W	1 ☐
Dimtype: non-dimmable		

Power box


of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	25510 0500 B INFORM SQ POWERBOX L 75W B	1 ☐
Dimtype: non-dimmable		
	25510 0500 W INFORM SQ POWERBOX L 75W W	1 ☐
	25510 0515 B INFORM SQ POWERBOX L 75W DIM5 B	1 ☐
Dimtype: DALI		
	25510 0515 W INFORM SQ POWERBOX L 75W DIM5 W	1 ☐






Coversets

	204 00 62 ANO COVERSET R 62 ANO	☐
	204 00 62 B COVERSET R 62 B	☐
	204 00 62 W COVERSET R 62 W	☐

DELTALIGHT

INFORM SQ P392-6 DOWN-UP 93067

25571 9320 B-B


	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT


INFORM SQ P392-6 DOWN-UP 93067

25571 9320 B-B

Suspension parts

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: