
DELTALIGHT




LOGIC LINEAR 440 94015

REFERENCE 30811 9410 N

AVAILABLE IN
ANTHRACITE 30811 9410 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	2
ADJUSTABILITY	non adjustable
INFORMATION	8 x LENS SP-15° INCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m INCL.IP68 CONNECTOR 3P ESG 8mm max.500kg

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 64) / 4000K / 1949lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	15°
LED TECHNICS (LIGHT SOURCE)	1949lm // 14,4W // 131lm/W
LED TECHNICS (LUMINAIRE)	1442lm // 17W // 87lm/W

Requirements

LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : **30811_XXX0_HAND.pdf**

DELTALIGHT

LOGIC LINEAR 440 94015

30811 9410 N

FINISH YOUR SPECIFICATION


Ground mounting boxes




30810 0010 LOGIC LINEAR 440 BOX

Cutout dimension (mm): 480 x 150

Waterproof connection parts



431 99 02 IP68 JUNCTION BOX 4P



21034 0150 IP68 Y-CONNECTOR 5P

Notes: