
DELTALIGHT




# M52 - SPY 52 92720 MDL

**REFERENCE** 24434 9220 W

AVAILABLE IN
**BLACK** 24434 9220 B
**FLEMISH BRONZE** 24434 9220 FBR
**FLEMISH GOLD** 24434 9220 FG
**GOLD COLOURED** 24434 9220 GC
**WHITE** 24434 9220 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Low voltage systems Low voltage system mounted |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.5 |
| **ADJUSTABILITY** | 0° to 90° swiveling, 355° rotatable |
| **INFORMATION** | REFLECTOR FL-20°<br>EXCL.LED POWER SUPPLY 48V-DC<br>Optional REFLECTORS 30° & 45° available |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | MDL = 1-10V or DALI or push button |
| **ENERGY CLASS** | E |
| **CERTIFICATES** | CB, ENEC, EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 1403lm // 12,4W // 113lm/W |
| **LED TECHNICS (LUMINAIRE)** | 879lm // 14W // 62lm/W |

**Remarks**

**Take a look at our MAGNETIC PROFILES movie**

**Requirements**

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

**Options**

DIMMABLE MODULATOR

**Accessories**

HONEYCOMB 42
SPREAD LENS 42

DELTALIGHT

# M52 - SPY 52 92720 MDL

24434 9220 W

LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual : **24434_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### Current supply

**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**21032 0030** SMART 48 MODULATOR PLUG-IN WD — 13


**Dimtype: WDL = wireless dimmable**

### SMART 48

**# of Fixtures**


**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




**300 90 011** SMART 48 MODULATOR DIM9 — 13

**Dimtype: 1-10V or DALI or push button**




**300 90 012** SMART 48 MODULATOR WD — 13

**Dimtype: WDL = wireless dimmable**

### LED power supplies


**# of Fixtures**

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


# M52 - SPY 52 92720 MDL

24434 9220 W





**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN — 7

**Dimtype: non-dimmable**




**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN — 16


**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W — 7

**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**





**21012 0240** LED POWER SUPPLY 48V-DC / 200W — 14


**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**


## Light altering devices




**19810 0010 B** HONEYCOMB 42 SINGLE USE B





**19810 0020** LINEAR SPREAD LENS 42




**19810 0030** SPREAD LENS 42





**19810 0040** SOFTENING LENS 42




**19810 0050** GLASS SBL 42

# M52 - SPY 52 92720 MDL

24434 9220 W




**19810 0060 B** HONEYCOMB 42 DOUBLE USE B

## Finish your product




**19810 0100 B** SPY 52 TUBE B

**19810 0100 FBR** SPY 52 TUBE FBR

**19810 0100 FG** SPY 52 TUBE FG

**19810 0100 GC** SPY 52 TUBE GC

**19810 0100 W** SPY 52 TUBE W

## Replaceable reflector / lens




**19810 0180** SPY 52 REFLECTOR 20°




**19810 0190** SPY 52 REFLECTOR 45°








**19810 0240** SPY 52 REFLECTOR 30°

DELTALIGHT

# M52 - SPY 52 92720 MDL

24434 9220 W

## COMPATIBLE COMPOSABLES

| SPLITLINE M52 profile | Available Colours |
|---|---|
|   **420 52 10 00** SPM52 - PROFILE 1m | |
|   **420 52 20 00** SPM52 - PROFILE 2m | |
|   **420 52 30 00** SPM52 - PROFILE 3m | |
|   **24413 0000** SPM52 - PROFILE | |

Notes: