



## OML50 - PRISMATIC LENS D TW 1968mm 950 DIM5

31629 9005 B

BESCHIKBAAR IN  
ZWART 31629 9005 B



[Bekijk op website](#)



### Algemene info

|                               |   |
|-------------------------------|---|
| <b>LOCATIE</b>                | binnen  |
| <b>STOF EN WATERDICHTHEID</b> | IP20  |
| <b>GEWICHT (KG)</b>           | 2.4   |
| <b>INFO</b>                   | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI DT8)<br>CABLING 1 CIRCUIT |

### Elektrische info

|                           |                      |
|---------------------------|----------------------|
| <b>ELEKTRISCH</b>         | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>             | I                    |
| <b>VOEDING INBEGREPEN</b> | YES                  |
| <b>DIM TYPE</b>           | DALI                 |
| <b>ENERGIE KLASSE</b>     | E                    |
| <b>CERTIFICATES</b>       | EPD, RCM             |

### Info lichtbron

|                                 |  |
|---------------------------------|--|
| <b>LIGHTSOURCE NAME</b>         | LED  |
| <b>LICHTBRON</b>                | @ 2700K: LED cluster 36W / CRI>90 (R9: 50) / 2700K-5000K / 4813lm<br>Or<br>@ 5000K: LED cluster 32,9W / CRI>90 (R9: 50) / 2700K-5000K / 5737lm |
| <b>SMDC</b>                     | SDCM3  |
| <b>RISK-GROEP</b>               | RG1  |
| <b>LM80</b>                     | L80 > 60000  |
| <b>LED TECHNIEK (LICHTBRON)</b> | @ 2700K: 4813lm // 36W // 134lm/W<br>Or<br>@ 5000K: 5737lm // 32,9W // 174lm/W   |

### Opties

WIRELESS CONTROL DIM5

Notes: