

OML50 - LED ARRAY DU HO CORNER X 930 DIM5

31067 9305


[View on website](#)


General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
INFORMATION	CLUSTER DOWN: 3863lm/m CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: 2 x (LED cluster 16,3W / CRI>90 (R9: 50) / 3000K / 2534lm) UP: 2 x (LED cluster 12,1W / CRI>90 (R9: 50) / 3000K / 1747lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 5068lm // 32,6W // 155lm/W UP: 3494lm // 24,2W // 145lm/W
Options	
WIRELESS CONTROL DIM5	

Notes: