



M26L - SPY 391 SOFT 93040 DIM5

23438 9035 W

AVAILABLE IN

BLACK 23438 9035 B

BRUSHED ALU 23438 9035 BRA

BRUSHED ANTHRACITE 23438 9035 BRAT

BRUSHED COPPER 23438 9035 BRCU

BRUSHED GOLD 23438 9035 BRG

BRUSHED OLD BRONZE 23438 9035 BROB

FLEMISH BRONZE 23438 9035 FBR

FLEMISH GOLD 23438 9035 FG

GOLD COLOURED 23438 9035 GC

PIANO BLACK 23438 9035 PB

WHITE 23438 9035 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements

SPY 39 TUBE

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23438_XXX5_HAND.pdf](#)

M26L - SPY 391 SOFT 93040 DIM5

23438 9035 W

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

20

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

8

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W

17

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FG SPY 39 TUBE FG

24144 0010 GC SPY 39 TUBE GC

24144 0010 W SPY 39 TUBE W

DELTALIGHT

M26L - SPY 391 SOFT 93040 DIM5

23438 9035 W




24144 0070 SPY 39 TUBE SBL




COMPATIBLE COMPOSABLES


SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
--	-------------------




23358 0000 SLM26L - PROFILE



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: