
DELTALIGHT




# MICROGRID IN 1 93015

**REFERENCE** 100055 9310 W-B

AVAILABLE IN
**BLACK-BLACK** 100055 9310 B-B
**BLACK-WHITE** 100055 9310 B-W
**WHITE-BLACK** 100055 9310 W-B
**WHITE-WHITE** 100055 9310 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | rectangle - 62 x 59 |
| **RECESSED DEPTH (MM)** | 75 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | min.12 - max.25 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.2 |
| **ADJUSTABILITY** | 0° to 20° swiveling, 350° rotatable |
| **INFORMATION** | LENS SP-15°<br>EXCL.LED POWER SUPPLY 350mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 3,9W / CRI>90 (R9: 55) / 3000K / 385lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 98 |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG2 (threshold 0,6m) |
| **LM80** | L90B10 > 41000 |
| **BEAMANGLE** | 15° |
| **LED TECHNICS (LIGHT SOURCE)** | 385lm // 3,9W // 98lm/W |
| **LED TECHNICS (LUMINAIRE)** | 288lm // 4W // 64lm/W |

**Requirements**

LED POWER SUPPLY 350mA-DC DIM

**Accessories**

MICRO VISOR

For detailed installation instructions, please consult the manual : **100055_XXX0_HAND.pdf**

DELTALIGHT

# MICROGRID IN 1 93015


100055 9310 W-B

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|---|
|  System ceiling | - |
|  Plasterboard | - |
|  Stucanet | - |
|  Wood | - |
|  Stretched ceiling | - |

## FINISH YOUR SPECIFICATION

### Emergency units



**21032 0270 B** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B ☐

**Cutout dimension (mm): 27**


**21032 0270 W** EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W ☐

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**



**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 3 ☐

**Dimtype: 1-10V**

**Cutout dimension (mm): 30**



**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3 ☐


**Dimtype: DALI**

**Cutout dimension (mm): 45**

DELTALIGHT

# MICROGRID IN 1 93015


100055 9310 W-B




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 3

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 3

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 — 3

**Dimtype: mains (phase cut-off) or push button**


**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 6(6)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 — 2->4(3)


**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**




**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 3


**Dimtype: 1-10V or DALI or push button**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 — 4(3)

**Dimtype: DALI**


**Cutout dimension (mm): 72**




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 — 2->9(10)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 — 2->4(3)

**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 — 4(3)


**Dimtype: DALI**

**Cutout dimension (mm): 55**

DELTALIGHT

# MICROGRID IN 1 93015


100055 9310 W-B




**300 90 135** LED POWER SUPPLY MULTI-POWER HV 5->7

**Dimtype: non-dimmable**


**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER 2->3

**Dimtype: non-dimmable**


**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1 4

**Dimtype: 1-10V**


**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5 4

**Dimtype: DALI**


**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL 6(6)

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL 4

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 54**




**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 2->2

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 50**




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 3->3

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 50**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 3

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68 4(3)


**Dimtype: non-dimmable**

**Cutout dimension (mm): 60**

DELTALIGHT

# MICROGRID IN 1 93015

100055 9310 W-B





**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 3

**Dimtype: DALI**

**Cutout dimension (mm): 30**

## Light altering devices




**10034 0010 B** MICRO VISOR B

Notes: