

## OML50 - LED ARRAY DU HO CORNER X 940 DIM5

31067 9405

 [View on website](#)


| General info                       |  |
|------------------------------------|--|
| <b>LOCATION</b>                    | indoor   |
| <b>INGRESS PROTECTION</b>          | IP20   |
| <b>WEIGHT (KG)</b>                 | 0  |
| <b>INFORMATION</b>                 | CLUSTER DOWN: 4029lm/m<br>CLUSTER UP: 2776lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT         |
| Electrical info                    |  |
| <b>ELECTRICAL</b>                  | 220-240V / 0 50-60Hz   |
| <b>CLASS</b>                       | I  |
| <b>POWER SUPPLY</b>                | YES  |
| <b>DIM TYPE</b>                    | DALI   |
| <b>ENERGY CLASS</b>                | D  |
| <b>CERTIFICATES</b>                | EPD, RCM   |
| Lightsource info                   |  |
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | DOWN: 2 x (LED cluster 16,3W / CRI>90 (R9: 50) / 4000K / 2643lm)<br>UP: 2 x (LED cluster 12,1W / CRI>90 (R9: 50) / 4000K / 1821lm) |
| <b>TM-30 VALUES</b>                | Rf: 90 / Rg: 101   |
| <b>SDCM</b>                        | SDCM3  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L80 > 60000  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 5286lm // 32,6W // 162lm/W<br>UP: 3642lm // 24,2W // 151lm/W   |
| Options                            |  |
| WIRELESS CONTROL DIM5              |  |

Notes: