
DELTALIGHT




# SPIX M PIN 93030

**REFERENCE** 29712 9330 N

AVAILABLE IN
**ANTHRACITE** 29712 9330 N
**PINE GREEN** 29712 9330 PGR




View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Surface mounted |
| **INGRESS PROTECTION** | IP65 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK05 |
| **WEIGHT (KG)** | 0.8 |
| **INFORMATION** | LENS FL-30°<br>INCL.1 x CABLE H05 RN-F 2 x 1 mm² 2m<br>EXCL.LED POWER SUPPLY 350-700mA-DC |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | G |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 3,9-8,2W / CRI>90 (R9: 55) / 3000K / 385-677lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 98 |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG2 (threshold 0,6m) |
| **LM80** | L90B10 > 41000 |
| **BEAMANGLE** | 30° |
| **LED TECHNICS (LIGHT SOURCE)** | 677lm // 8,2W // 83lm/W |
| **LED TECHNICS (LUMINAIRE)** | 454lm // 9W // 48lm/W |

**Requirements**

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

**Options**

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

**Accessories**

KAP STRIPER

# SPIX M PIN 93030

29712 9330 N

For detailed installation instructions, please consult the manual : **29712_XXX0_HAND.pdf**


## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


**Min current | Max current**




**300 48 350 ED1** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 — 3

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 350 ED5** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 350 MDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL — 3

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 350 WDL** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL — 3

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 48 500 ED1** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 — 3

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 500 ED5** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3

**Dimtype: DALI**

**Cutout dimension (mm): 45**





**300 48 500 MDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL — 3

**Dimtype: non-dimmable**

**Cutout dimension (mm): 30**

# SPIX M PIN 93030


29712 9330 N




**300 48 500 WDL** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL — 3

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 48 700 ED1** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 — 3

**Dimtype: 1-10V**


**Cutout dimension (mm): 30**




**300 48 700 ED5** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 3

**Dimtype: DALI**


**Cutout dimension (mm): 45**




**300 48 700 MDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL — 3

**Dimtype: non-dimmable**


**Cutout dimension (mm): 30**




**300 48 700 WDL** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL — 3

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 45**




**300 90 61** LED POWER SUPPLY MULTI-POWER DIM6 — 3 | 3 | 3

**Dimtype: mains (phase cut-off) or push button**


**Cutout dimension (mm): 56**




**300 90 63** LED POWER SUPPLY MULTI-POWER DIM9 — 6(6) | 6(6) | 6(4)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 82**




**300 90 64** LED POWER SUPPLY MULTI-POWER DIM7 — 2->4(3) | 4(2) | 3(1)


**Dimtype: 1-10V or push button**

**Cutout dimension (mm): 72**




**300 90 67** LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 — 3 | 3

**Dimtype: 1-10V or DALI or push button**




**300 90 68** LED POWER SUPPLY MULTI-POWER DIM5 — 4(3) | 4(2) | 3(1)


**Dimtype: DALI**

**Cutout dimension (mm): 72**

DELTALIGHT

# SPIX M PIN 93030


29712 9330 N




**300 90 69** LED POWER SUPPLY MULTI-POWER HV DIM9 2->9(10) | 9(6) | 7(4)

**Dimtype: 1-10V or DALI or push button**


**Cutout dimension (mm): 84**




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7 2->4(3) | 3(2) | 2(1)

**Dimtype: 1-10V or push button**


**Cutout dimension (mm): 55**




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5 4(3) | 3(2) | 2(1)

**Dimtype: DALI**


**Cutout dimension (mm): 55**




**300 90 135** LED POWER SUPPLY MULTI-POWER HV 5->7 | 4->7 | 4->6 | 3->6

**Dimtype: non-dimmable**


**Cutout dimension (mm): 90**




**21012 0010** LED POWER SUPPLY MULTI POWER 2->3 | 3 | 3

**Dimtype: non-dimmable**


**Cutout dimension (mm): 50**




**21012 0021** LED POWER SUPPLY MULTI POWER DIM1 4 | 4 | 4

**Dimtype: 1-10V**


**Cutout dimension (mm): 54**




**21012 0035** LED POWER SUPPLY MULTI POWER DIM5 4 | 4 | 4

**Dimtype: DALI**


**Cutout dimension (mm): 54**




**21012 004W** LED POWER SUPPLY MULTI-POWER WDL 6(6) | 5(5) | 5(4)

**Dimtype: WDL = wireless dimmable**


**Cutout dimension (mm): 84**




**21012 005W** LED POWER SUPPLY MULTI-POWER COMPACT WDL 4 | 4 | 4

**Dimtype: WDL = wireless dimmable**

**Cutout dimension (mm): 54**





**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 2->2

**Dimtype: mains (phase cut-off)**

**Cutout dimension (mm): 50**

# SPIX M PIN 93030


29712 9330 N




**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 — 3->3

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 50**




**21012 0278** LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 — 2->2 | 2->2

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 55**




**21012 0288** LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 — 3->4 | 3->4

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 55**




**21012 0298** LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 — 3 | 3 | 2

**Dimtype: mains (phase cut-off)**


**Cutout dimension (mm): 48**




**21012 0480** LED POWER SUPPLY 350mA-DC / 17W IP68 — 4(3)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 60**




**21012 0490** LED POWER SUPPLY 700mA-DC / 30W IP68 — 3(1)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 60**




**21012 0500** LED POWER SUPPLY 500mA-DC / 24W IP68 — 4(2)

**Dimtype: non-dimmable**


**Cutout dimension (mm): 60**




**21032 0295** LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 — 3

**Dimtype: DALI**


**Cutout dimension (mm): 30**




**21032 0305** LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 — 3

**Dimtype: DALI**

**Cutout dimension (mm): 30**




**21032 0315** LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 3

**Dimtype: DALI**


**Cutout dimension (mm): 30**

DELTALIGHT

# SPIX M PIN 93030


29712 9330 N

## Waterproof connection parts




**216 12 00** CBOX

**Cutout dimension (mm): 142 x 142**





**216 12 01** IP68 CONNECTION KIT




**216 12 02** IP68 CONNECTOR 3P

## Light altering devices




**223 00 10 B** KAP STRIPER B

Notes: