



SUPERLOOP SLIM IN 170 SBL 930

20575 9300 GC

AVAILABLE IN


NOIR 20575 9300 B

FLEMISH BRONZE 20575 9300 FBR

FLEMISH GOLD 20575 9300 FG

COULEUR OR 20575 9300 GC

BLANC 20575 9300 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Suspendu
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.4
ADJUSTABILITY	non réglable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 1200-1700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 51,7-71,4W / CRI>90 (R9: 59) / 3000K / 7128-9460lm
SDMC	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	9460lm // 71,4W // 132lm/W
LED TECHNICS (LUMINAIRE)	4188lm // 82,1W // 51lm/W

Requirements

LED POWER SUPPLY 1200 / 1700mA-DC DIM
SUPERLOOP POWERBOX H 1200mA
SUPERLOOP POWERBOX H 1700mA


Options



CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual : [20575_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Power box		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B Dimtype: 1 à 10 V	1 ☐
	321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W	1 ☐
	321 55 317 ED1 B SUPERLOOP POWERBOX H8 1700mA DIM1 B Dimtype: 1 à 10 V	1 ☐
	321 55 317 ED1 W SUPERLOOP POWERBOX H8 1700mA DIM1 W	1 ☐

DELTALIGHT

SUPERLOOP SLIM IN 170 SBL 930

20575 9300 GC



20548 0025 B

SUPERLOOP POWERBOX H9 1200mA DIM5 B

1

☐

Dimtype: DALI

20548 0025 W

SUPERLOOP POWERBOX H9 1200mA DIM5 W

1

☐


les alimentations led

of Fixtures



web2print_power_supply_info_box

Min current | Max current



300 90 130


LED POWER SUPPLY 1200mA-DC / 60W DIM5

1

☐

Dimtype: DALI

Cutout dimension (mm): 95



300 90 132


LED POWER SUPPLY 1200mA-DC / 70W DIM1

1

☐

Dimtype: 1 à 10 V

Cutout dimension (mm): 80



300 90 133


LED POWER SUPPLY 1700mA-DC / 99W DIM1

1

☐

Dimtype: 1 à 10 V

Cutout dimension (mm): 80



21012 0475


LED POWER SUPPLY 1700mA-DC / 92W DIM5

1

☐

Dimtype: DALI

les sets pour recouvrement plafond



204 00 62 ANO

COVERSET R 62 ANO

☐

204 00 62 B

COVERSET R 62 B

☐

204 00 62 W

COVERSET R 62 W

☐

DELTALIGHT

SUPERLOOP SLIM IN 170 SBL 930

20575 9300 GC

	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERLOOP SLIM IN 170 SBL 930

20575 9300 GC

les accessoires de suspension

	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0340 B SUSPENSION ST B	☐
Cutout dimension (mm): 27		
	15225 0340 W SUSPENSION ST W	☐

les accessoires pour connexions électriques

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
Cutout dimension (mm): 62 (CONCRETE: 102)		
	15225 0360 B CONNECTION ST B	☐
Cutout dimension (mm): 43		
	15225 0360 W CONNECTION ST W	☐

Notes: