
DELTALIGHT




ENTERO RD-M TRIMLESS TW 96530

REFERENCE 28432 9020 B

AVAILABLE IN
BLACK 28432 9020 B
FULL WHITE 28432 9020 FW
GOLD COLOURED 28432 9020 GC





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 45° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	787lm // 10W // 76lm/W

Requirements

MOUNTING KIT ENTERO ROUND M
LED POWER SUPPLY 500mA-DC TW (Remote)

Accessories

ENTERO M HONEYCOMB
ENTERO M LINEAR SPREAD LENS
ENTERO M SPREAD LENS
ENTERO M SOFTENING LENS
ENTERO M GLASS SBL

DELTALIGHT

ENTERO RD-M TRIMLESS TW 96530

28432 9020 B

For detailed installation instructions, please consult the manual : **28432_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Plasterboard**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Stucanet**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Concrete + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Lintel + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Hollow-core slab + plaster**	28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 **Stretched ceiling**	28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required
	28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 2

Dimtype: DALI


Cutout dimension (mm): 85

DELTALIGHT

ENTERO RD-M TRIMLESS TW 96530

28432 9020 B


Mounting kits



28400 0020 MOUNTING KIT ENTERO RD-M O.F.A.

Cutout dimension (mm): 127

Mounting kits stretched ceiling



28400 0080 MOUNTING KIT ENTERO RD-M CSC



28400 0140 MOUNTING KIT ENTERO RD-M WSC

Light altering devices



28500 0070 ENTERO M LINEAR SPREAD LENS




28500 0080 ENTERO M SPREAD LENS



28500 0090 ENTERO M SOFTENING LENS



28500 0100 ENTERO M GLASS SBL




28500 0110 B ENTERO M HONEYCOMB SINGLE USE B

DELTALIGHT

ENTERO RD-M TRIMLESS TW 96530

28432 9020 B



28500 0120 B ENTERO M HONEYCOMB DOUBLE USE B

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°



24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°

Notes: