
DELTALIGHT




INFORM ST 828 93067

REFERENCE 25501 9320 W-B

AVAILABLE IN
BLACK-BLACK 25501 9320 B-B
BLACK-FLEMISH GOLD 25501 9320 B-FG
WHITE-BLACK 25501 9320 W-B
WHITE-WHITE 25501 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 841
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 300/450mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 3000K / 1602-2315lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2315lm // 16,7W // 138lm/W
LED TECHNICS (LUMINAIRE)	2021lm // 19W // 105lm/W

Requirements

INFORM POWER SUPPLY 17W

For detailed installation instructions, please consult the manual : **25501_XXX0_HAND.pdf**

DELTALIGHT

INFORM ST 828 93067

25501 9320 W-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Wood**	-


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



25510 0375 INFORM POWER SUPPLY 17W DIM5 — 1

Dimtype: DALI



25510 0420 INFORM POWER SUPPLY 17W — 1

Dimtype: non-dimmable

Notes: