



## LOGIC W S 930

304 33 811 930 W

AVAILABLE IN



**ALU GREY** 304 33 811 930 A

**BLACK** 304 33 811 930 B

**FLEMISH BRONZE OUTDOOR** 304 33 811 930 FBRX

**ANTHRACITE** 304 33 811 930 N

**WHITE** 304 33 811 930 W



[View on website](#)



| General info                         |                                                                |
|--------------------------------------|----------------------------------------------------------------|
| LOCATION                             | indoor-outdoor                                                 |
| INSTALLATION                         | Wall Recessed                                                  |
| CUTOUT SHAPE/SIZE (MM)               | rectangle - BOX                                                |
| RECESSED DEPTH (MM)                  | 115-140                                                        |
| INGRESS PROTECTION                   | IP65                                                           |
| PROTECTION AGAINST MECHANICAL IMPACT | IK03                                                           |
| WEIGHT (KG)                          | 0.7                                                            |
| ADJUSTABILITY                        | non adjustable                                                 |
| INFORMATION                          | INCL.PC SBL<br>INCL.LED POWER SUPPLY 350mA-DC<br>INCL.1 x PG11 |

| Electrical info |                    |
|-----------------|--------------------|
| ELECTRICAL      | 110-240V / 50-60Hz |
| CLASS           | I                  |
| POWER SUPPLY    | YES                |
| DIM TYPE        | non-dimmable       |
| ENERGY CLASS    | D                  |

| Lightsource info            |                                                  |
|-----------------------------|--------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                              |
| LIGHTSOURCE                 | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| TM-30 VALUES                | Rf: 90 / Rg: 99                                  |
| SDCM                        | SDCM1                                            |
| RISKGROUP                   | RG1                                              |
| LM80                        | L90B10 > 50000                                   |
| LED TECHNICS (LIGHT SOURCE) | 787lm // 5,8W // 135lm/W                         |
| LED TECHNICS (LUMINAIRE)    | 172lm // 6,7W // 26lm/W                          |

### Requirements


CONCRETE BOX 192

CONCRETE PACK LOGIC W S

For detailed installation instructions, please consult the manual : [304\\_33\\_811\\_XXX\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Concrete boxes




**270 11 192** CONCRETE BOX 192

☐

Cutout dimension (mm): 135 x 125

Concrete packs



**304 33 96** CONCRETE PACK LOGIC W S

☐

Cutout dimension (mm): 135 x 125

Notes: