
DELTALIGHT




COMPO M TW 96541

REFERENCE 9 15729 9030 DC

AVAILABLE IN
BLACK 9 15729 9030 B
CHROMED 9 15729 9030 C
DARK CHROMED 9 15729 9030 DC
WHITE 9 15729 9030 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.266
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,8W / CRI>90 (R9: 50) / 2700K-6500K / 1383lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1383lm // 11,8W // 118lm/W
LED TECHNICS (LUMINAIRE)	1070lm // 14W // 79lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO M HONEYCOMB SINGLE USE B
COMPO M LINEAR SPREAD LENS
COMPO M SPREAD LENS
COMPO M SOFTENING LENS
COMPO M GLASS SBL

For detailed installation instructions, please consult the manual : **9_15729_XXX0_HAND.pdf**

DELTALIGHT

COMPO M TW 96541

9 15729 9030 DC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Plasterboard	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 Wood	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

15710 5900	LED POWER SUPPLY MULTIPOWER 12W DALI DT8 500mA	1 ☐
15710 6400	LED POWER SUPPLY MULTIPOWER 20W DALI DT8 350mA	1 ☐

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B ☐

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W ☐



15710 0050 MOUNTING KIT COMPO M TRIMLESS ☐

Cutout dimension (mm): 76

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B ☐

DELTALIGHT

COMPO M TW 96541

9 15729 9030 DC

15710 1110 COMPO M LINEAR SPREAD LENS ☐

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS ☐

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS ☐

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL ☐

Cutout dimension (mm): 32,5

Notes: