



OML50 - INFORM DU HE 3280mm 8+16+8LED 94063

31445 9430 B

BESCHIKBAAR IN
ZWART 31445 9430 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.7
INFO	CLUSTER DOWN: 1612lm/m CLUSTER UP: 2015lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm UP: LED cluster 40,8W / CRI>90 (R9: 50) / 4000K / 6608lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 5286lm // 32,6W // 162lm/W UP: 6608lm // 40,8W // 162lm/W

Notes: