

OML50 - LED ARRAY DU HE CORNER L 930 DIM5

31068 9305

 [Bekijk op website](#)


Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.4
INFO	CLUSTER DOWN: 2780lm/m CLUSTER UP: 1932lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT
Elektrische info	
INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1824lm) UP: 2 x (LED cluster 8,2W / CRI>90 (R9: 50) / 3000K / 1267lm)
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3648lm // 22,2W // 164lm/W UP: 2534lm // 16,4W // 155lm/W
Opties	
WIRELESS CONTROL DIM5	

Notes: