
DELTALIGHT




SOLI - 66 NLT 952718 MDL

REFERENCE 27122 7210 B

AVAILABLE IN
BLACK 27122 7210 B
WHITE 27122 7210 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 48V-DC NLT = Natural Light Technology Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21,1W / CRI>95 (R9: 96) / 2700K / 1925lm
TM-30 VALUES	Rf: 97 / Rg: 102
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	1925lm // 21,1W // 91lm/W
LED TECHNICS (LUMINAIRE)	1375lm // 24,3W // 57lm/W

Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

DELTALIGHT

SOLI - 66 NLT 952718 MDL

27122 7210 B

For detailed installation instructions, please consult the manual : **27122_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 7

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 7


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 4

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 9

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 4


Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SOLI - 66 NLT 952718 MDL

27122 7210 B




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 8

Dimtype: non-dimmable

Cutout dimension (mm): 40


Light altering devices




24611 0150 B HONEYCOMB 57 SINGLE USE B




24611 0160 GLASS SBL 57




24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57




24611 0200 SPREAD LENS 57



24611 0210 B HONEYCOMB 57 DOUBLE USE B

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

SOLI - 66 NLT 952718 MDL



27122 7210 B

24611 0100 FG	SPY 66 TUBE FG	☐
24611 0100 GC	SPY 66 TUBE GC	☐
24611 0100 W	SPY 66 TUBE W	☐

Replaceable reflector / lens

	**24611 0220** SPY 66 REFLECTOR 18°	☐
	**24611 0230** SPY 66 REFLECTOR 30°	☐
	**24611 0240** SPY 66 REFLECTOR 45°	☐

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 **27111 0020** SOLI - PROFILE 2m	● ○
 **27111 0030** SOLI - PROFILE 3m	● ○

Notes: