



SUPERLOOP SLIM OUT 120 SBL 927

20578 9200 W

AVAILABLE IN


BLACK 20578 9200 B

FLEMISH BRONZE 20578 9200 FBR

FLEMISH GOLD 20578 9200 FG

GOLD COLOURED 20578 9200 GC

WHITE 20578 9200 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL EXCL.LED POWER SUPPLY 900-1200mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 3.0m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 36,4-50,3W / CRI>90 (R9: 59) / 2700K / 5022-6665lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	6665lm // 50,3W // 132lm/W
LED TECHNICS (LUMINAIRE)	2951lm // 57,8W // 51lm/W

Requirements

LED POWER SUPPLY 900 / 1200mA-DC DIM
SUPERLOOP POWERBOX H 900mA
SUPERLOOP POWERBOX H 1200mA

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 927

20578 9200 W

For detailed installation instructions, please consult the manual : [20578_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐

203 99 56 ANO CABLE BASE S ANO

☐

203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐


Power box

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



321 55 312 ED1 B SUPERLOOP POWERBOX H8 1200mA DIM1 B


1

☐

Dimtype: 1-10V

321 55 312 ED1 W SUPERLOOP POWERBOX H8 1200mA DIM1 W

1

☐

20548 0015 B SUPERLOOP POWERBOX H9 900mA DIM5 B

1

☐

Dimtype: DALI

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 927

20578 9200 W

	<u>20548 0015 W</u>	SUPERLOOP POWERBOX H9 900mA DIM5 W	1	☐
	<u>20548 0025 B</u>	SUPERLOOP POWERBOX H9 1200mA DIM5 B	1	☐
	Dimtype: DALI			
	<u>20548 0025 W</u>	SUPERLOOP POWERBOX H9 1200mA DIM5 W	1	☐

LED power supplies

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

	<u>300 90 129</u>	LED POWER SUPPLY 900mA-DC / 60W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 84			
	<u>300 90 130</u>	LED POWER SUPPLY 1200mA-DC / 60W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 95			
	<u>300 90 132</u>	LED POWER SUPPLY 1200mA-DC / 70W DIM1	1	☐
	Dimtype: 1-10V			
	Cutout dimension (mm): 80			





Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO		☐
	<u>204 00 62 B</u>	COVERSET R 62 B		☐
	<u>204 00 62 W</u>	COVERSET R 62 W		☐

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 927

20578 9200 W


	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐
	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

DELTALIGHT

SUPERLOOP SLIM OUT 120 SBL 927

20578 9200 W


Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0340 B SUSPENSION ST B


☐

Cutout dimension (mm): 27

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Cutout dimension (mm): 62 (CONCRETE: 102)



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: