
DELTALIGHT




LOGIC LINEAR ON 440 HONEYCOMB 92740 DIM5

REFERENCE 30828 9235 N

AVAILABLE IN
ALU GREY 30828 9235 A
BLACK 30828 9235 B
FLEMISH BRONZE OUTDOOR 30828 9235 FBRX
ANTHRACITE 30828 9235 N
WHITE 30828 9235 W





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK07
WEIGHT (KG)	1
INFORMATION	8 x LENS WFL-40° INCL.HONEYCOMB EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,4W / CRI>90 (R9: 55) / 2700K / 1644lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1644lm // 14,4W // 111lm/W
LED TECHNICS (LUMINAIRE)	841lm // 16,6W // 51lm/W

Requirements

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

Options

THROUGH WIRING SET IP68

DELTALIGHT

LOGIC LINEAR ON 440 HONEYCOMB 92740 DIM5

30828 9235 N

For detailed installation instructions, please consult the manual : **30828_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0390 LED POWER SUPPLY 48V-DC / 90W — 5

Dimtype: non-dimmable

Cutout dimension (mm): 75

Fixation components



30810 0040 LOGIC LINEAR 880 BOX EXTEND


30810 0040 INOX WALL BRACKET SET 60 INOX

30810 0040 N WALL BRACKET SET 60 N



30810 0050 INOX WALL BRACKET SET 100 INOX

30810 0050 N WALL BRACKET SET 100 N



30810 0060 INOX WALL BRACKET SET 200 INOX

30810 0060 N WALL BRACKET SET 200 N

DELTALIGHT

LOGIC LINEAR ON 440 HONEYCOMB 92740 DIM5

30828 9235 N



30810 0070 INOX FLOOR BRACKET SET INOX

Electric connection parts



30810 0080 IP68 CABLE + CONNECTOR 5P - 0,5m



30810 0090 IP68 CABLE + CONNECTOR 5P - 2m



30810 0100 THROUGH WIRING SET IP68 440

Notes: