
DELTALIGHT




D-LINER 30 SBL LOC2 1390 940 DIM5

REFERENCE 32075 9405 B

AVAILABLE IN
BLACK 32075 9405 B
WHITE 32075 9405 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 780mA-DC INCL.1 x CABLE 5 x 0,75mm² - 0,5m + WIELAND PLUG GST18i5 male pastelblue

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 30W / CRI>90 (R9: 60) / 4000K / 4020lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	4020lm // 30W // 136lm/W
LED TECHNICS (LUMINAIRE)	2553lm // 34,5W // 74lm/W

For detailed installation instructions, please consult the manual : **32075_XXX5_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
Acoustic climate-control ceiling Hunter Douglas 30BD	-

DELTALIGHT

D-LINER 30 SBL LOC2 1390 940 DIM5

32075 9405 B

Notes: