

INFORM ST 828 94067

25501 9420 B-B


AVAILABLE IN

BLACK-BLACK 25501 9420 B-B

BLACK-FLEMISH GOLD 25501 9420 B-FG

WHITE-BLACK 25501 9420 W-B

WHITE-WHITE 25501 9420 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 841
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	36 x REFLECTOR FL-67° EXCL. LED POWER SUPPLY 300/450mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 10,5-16,7W / CRI>90 (R9: 50) / 4000K / 1670-2416lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2416lm // 16,7W // 144lm/W
LED TECHNICS (LUMINAIRE)	2109lm // 19,2W // 110lm/W

Requirements



INFORM POWER SUPPLY 17W

For detailed installation instructions, please consult the manual : [25501_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -
	Wood -

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	25510 0375 INFORM POWER SUPPLY 17W DIM5	1
Dimtype: DALI		
	25510 0420 INFORM POWER SUPPLY 17W	1
Dimtype: non-dimmable		

Notes: