DELTALIGHT



# LOGIC LINEAR ON 440 92725 DIM5

**REFERENCE** 30827 9225 W

AVAILABLE IN
**ALU GREY** 30827 9225 A
**BLACK** 30827 9225 B
**FLEMISH BRONZE OUTDOOR** 30827 9225 FBRX
**ANTHRACITE** 30827 9225 N
**WHITE** 30827 9225 W







View on website

| General info | |
|---|---|
| **LOCATION** | outdoor |
| **INSTALLATION** | Floor Surface mounted,Wall Surface mounted |
| **INGRESS PROTECTION** | IP67 |
| **PROTECTION AGAINST MECHANICAL IMPACT** | IK07 |
| **WEIGHT (KG)** | 1 |
| **INFORMATION** | 8 x LENS FL-25°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 48V-DC |
| **CLASS** | III |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | F |
| **CERTIFICATES** | CB, ENEC |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 14,4W / CRI>90 (R9: 55) / 2700K / 1644lm |
| **TM-30 VALUES** | Rf: 91 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG2 |
| **LM80** | L80 > 150000 |
| **BEAMANGLE** | 25° |
| **LED TECHNICS (LIGHT SOURCE)** | 1644lm // 14,4W // 111lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1361lm // 17W // 82lm/W |

**Requirements**

WALL BRACKET SET
FLOOR BRACKET SET
IP68 CABLE + CONNECTOR 5P
LED POWER SUPPLY 48V-DC

**Options**

THROUGH WIRING SET IP68

DELTALIGHT

# LOGIC LINEAR ON 440 92725 DIM5

30827 9225 W

For detailed installation instructions, please consult the manual : **30827_XXX5_HAND.pdf**

## FINISH YOUR SPECIFICATION

### LED power supplies

### # of Fixtures

# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**Min current | Max current**




**21032 0390** LED POWER SUPPLY 48V-DC / 90W — 5

**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**

### Fixation components



**30810 0040** LOGIC LINEAR 880 BOX EXTEND

**30810 0040 INOX** WALL BRACKET SET 60 INOX

**30810 0040 N** WALL BRACKET SET 60 N



**30810 0050 INOX** WALL BRACKET SET 100 INOX

**30810 0050 N** WALL BRACKET SET 100 N



**30810 0060 INOX** WALL BRACKET SET 200 INOX

**30810 0060 N** WALL BRACKET SET 200 N

DELTALIGHT

# LOGIC LINEAR ON 440 92725 DIM5

30827 9225 W



**30810 0070 INOX** FLOOR BRACKET SET INOX

## Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m



**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m



**30810 0100** THROUGH WIRING SET IP68 440

Notes: