DELTALIGHT



# OML50 - LED ARRAY DU HE 984mm 930 DIM5

**REFERENCE** 31040 9305

View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 1.1 |
| **INFORMATION** | CLUSTER DOWN: 2780lm/m<br>CLUSTER UP: 1932lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 0\|50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | D |
| **CERTIFICATES** | EPD, RCM |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | DOWN: LED cluster 16,7W / CRI>90 (R9: 50) / 3000K / 2736lm<br>UP: LED cluster 12,2W / CRI>90 (R9: 50) / 3000K / 1901lm |
| **TM-30 VALUES** | Rf: 92 / Rg: 100 |
| **SDCM** | SDCM3 |
| **RISKGROUP** | RG1 |
| **LM80** | L80 > 60000 |
| **LED TECHNICS (LIGHT SOURCE)** | DOWN: 2736lm // 16,7W // 164lm/W<br>UP: 1901lm // 12,2W // 155lm/W |

**Options**

WIRELESS CONTROL DIM5

Notes: