



M26L - SPY 391 SOFT 93020 MDL

23437 9020 PB

AVAILABLE IN

BLACK 23437 9020 B

BRUSHED ALU 23437 9020 BRA

BRUSHED ANTHRACITE 23437 9020 BRAT

BRUSHED COPPER 23437 9020 BRCU

BRUSHED GOLD 23437 9020 BRG

BRUSHED OLD BRONZE 23437 9020 BROB


FLEMISH BRONZE 23437 9020 FBR

FLEMISH GOLD 23437 9020 FG

GOLD COLOURED 23437 9020 GC

PIANO BLACK 23437 9020 PB

WHITE 23437 9020 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATION	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M26L - SPY 391 SOFT 93020 MDL

23437 9020 PB

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 web2print_power_supply_info_box

Min current | Max current



21032 0030

SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 90 011

SMART 48 MODULATOR DIM9

16

Dimtype: 1-10V or DALI or push button



300 90 012

SMART 48 MODULATOR WD

16


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 89 48 100

LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non-dimmable



300 89 48 240

LED POWER SUPPLY 48V-DC / 240W DIN


20

Dimtype: non-dimmable


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL



23437 9020 PB

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 40		

Finish your product

	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FG SPY 39 TUBE FG	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	☐ ☐
	☐ ☐


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL

23437 9020 PB



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: