



M26L - SPY 391 SOFT 93020 MDL

23437 9020 PB

AVAILABLE IN

SCHWARZ 23437 9020 B

ALU GEBÜSTET 23437 9020 BRA

GEBÜSTETES ANTHRAZIT 23437 9020 BRAT

GEBÜSTETES KUPFER 23437 9020 BRCU

GEBÜSTETES GOLD 23437 9020 BRG

GEBÜSTETE ALTE BRONZE 23437 9020 BROB



FLEMISH BRONZE 23437 9020 FBR

FLEMISH GOLD 23437 9020 FG

GOLDFARBEN 23437 9020 GC

KLAVIER SCHWARZ 23437 9020 PB

WEISS 23437 9020 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Niederspannungssysteme Niederspannungssysteme montiert
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° schwenkbar, 360° drehbar
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V, DALI / Taster
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Stromversorgung

of Fixtures

Min current | Max current

of fixtures

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = Drahtlos dimmbar

16


SMART 48

of Fixtures

Min current | Max current

of fixtures


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

Dimtype: 1-10V, DALI / Taster

16



300 90 012 SMART 48 MODULATOR WD

Dimtype: WDL = Drahtlos dimmbar

16


LED Betriebsgeräte

of Fixtures

Min current | Max current

of fixtures

Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN




Dimtype: nicht dimmbar

8


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL


23437 9020 PB

	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	20	☐
Dimtype: nicht dimmbar			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8	☐
Dimtype: nicht dimmbar			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17	☐
Dimtype: nicht dimmbar			
Cutout dimension (mm): 40			

Beenden Sie Ihr Produkt

	24144 0010 B SPY 39 TUBE B	☐
	24144 0010 FBR SPY 39 TUBE FBR	☐
	24144 0010 FG SPY 39 TUBE FG	☐
	24144 0010 GC SPY 39 TUBE GC	☐
	24144 0010 W SPY 39 TUBE W	☐
	24144 0070 SPY 39 TUBE SBL	☐


COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
	 
23358 0000 SLM26L - PROFILE	


DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL


23437 9020 PB



23358 0010 SLM26L - PROFILE 1m



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: