




OML50 - INFORM DU HE 3280mm
8+16+8LED 94063 DIM5

31445 9435 B

AVAILABLE IN
BLACK 31445 9435 B

 [View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.4
INFORMATION	CLUSTER DOWN: 1612lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm UP: LED cluster 40,8W / CRI>90 (R9: 50) / 4000K / 6608lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN: 5286lm // 32,6W // 162lm/W UP: 6608lm // 40,8W // 162lm/W

Options
WIRELESS CONTROL DIM5

Notes: