





SUPERNOVA FLAT 65 SMOOTH UP 930

20632 9300 B

AVAILABLE IN

BLACK 20632 9300 B

WHITE 20632 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	8.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.ADJUSTABLE LED POWER SUPPLY - 2 settings: 1- 1400mA 2- 930mA

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 58,5W / CRI>90 (R9: 68) / 3000K / 7776lm Or LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm
TM-30 VALUES	Rf: 89 / Rg: 97 rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	7776lm // 58,5W // 132lm/W Or 5360lm // 37,4W // 144lm/W
LED TECHNICS (LUMINAIRE)	6151lm // 67,3W // 91lm/W Or 4240lm // 43W // 99lm/W


Options

SUSPENSION SET 25 3m
CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT

For detailed installation instructions, please consult the manual : [20632_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO

CABLE BASE R ANO

☐

203 99 55 B

CABLE BASE R B

☐

203 99 55 W

CABLE BASE R W

☐



203 99 56 ANO

CABLE BASE S ANO

☐

203 99 56 B

CABLE BASE S B


☐

203 99 56 W

CABLE BASE S W

☐

Coversets



204 00 62 ANO

COVERSET R 62 ANO

☐

204 00 62 B


COVERSET R 62 B

☐

204 00 62 W

COVERSET R 62 W

☐



204 00 90 ANO





COVERSET R 90 ANO

☐

DELTALIGHT

SUPERNOVA FLAT 65 SMOOTH UP 930

20632 9300 B

	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐
	<u>204 80 80 W</u>	COVERSET S 80 W	☐
	<u>204 90 90 ANO</u>	COVERSET S 90 ANO	☐
	<u>204 90 90 B</u>	COVERSET S 90 B	☐
	<u>204 90 90 W</u>	COVERSET S 90 W	☐

DELTALIGHT

SUPERNOVA FLAT 65 SMOOTH UP 930

20632 9300 B


Suspension parts




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

☐

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W

☐

328 25 43 SUSPENSION SET 25 3m

☐

328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

☐

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

☐

Electric connection parts



15225 0360 B CONNECTION ST B

☐

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

☐

Notes: