





INFORM R3 DOWN-UP 92748

REFERENCE 26823 9220 W-W

AVAILABLE IN
BLACK-BLACK 26823 9220 B-B
BLACK-FLEMISH GOLD 26823 9220 B-FG
FLEMISH GOLD-BLACK 26823 9220 FG-B
WHITE-BLACK 26823 9220 W-B
WHITE-WHITE 26823 9220 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.2
ADJUSTABILITY	non adjustable
INFORMATION	168 x REFLECTOR WFL-71° (DOWN) EXCL.2 x LED POWER SUPPLY 1050mA-DC (DOWN/UP) INCL.7 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm ²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	C
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 33,9W / CRI>90 (R9: 50) / 2700K / 5208lm UP: LED cluster 17W / CRI>90 (R9: 50) / 2700K / 2604lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	DOWN: 5208lm // 33,9W // 153lm/W UP: 2604lm // 17W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 4161lm // 39W // 107lm/W UP: 1667lm // 19,6W // 85lm/W


Requirements	
LED POWER SUPPLY 1050mA-DC DIM (Remote)	

Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

For detailed installation instructions, please consult the manual : [26823_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply


	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current






	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1 down 1 up ☐
Dimtype: 1-10V or DALI or push button		
Cutout dimension (mm): 82		

DELTALIGHT

INFORM R3 DOWN-UP 92748

26823 9220 W-W



Coversets

	<u>204 00 62 ANO</u>	COVERSET R 62 ANO	☐
	<u>204 00 62 B</u>	COVERSET R 62 B	☐
	<u>204 00 62 W</u>	COVERSET R 62 W	☐
	<u>204 00 90 ANO</u>	COVERSET R 90 ANO	☐
	<u>204 00 90 B</u>	COVERSET R 90 B	☐
	<u>204 00 90 W</u>	COVERSET R 90 W	☐
	<u>204 00 100 ANO</u>	COVERSET R 100 ANO	☐
	<u>204 00 100 B</u>	COVERSET R 100 B	☐
	<u>204 00 100 W</u>	COVERSET R 100 W	☐
	<u>204 62 62 ANO</u>	COVERSET S 62 ANO	☐
	<u>204 62 62 B</u>	COVERSET S 62 B	☐
	<u>204 62 62 W</u>	COVERSET S 62 W	☐
	<u>204 80 80 ANO</u>	COVERSET S 80 ANO	☐
	<u>204 80 80 B</u>	COVERSET S 80 B	☐


DELTALIGHT

INFORM R3 DOWN-UP 92748


26823 9220 W-W

	204 80 80 W	COVERSET S 80 W	☐
	204 90 90 ANO	COVERSET S 90 ANO	☐
	204 90 90 B	COVERSET S 90 B	☐
	204 90 90 W	COVERSET S 90 W	☐

Suspension parts

	328 10 01	SUSPENSION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	15225 0340 B	SUSPENSION ST B	☐
		Cutout dimension (mm): 27	
	15225 0340 W	SUSPENSION ST W	☐

Electric connection parts

	328 10 03	CONNECTION TRIMLESS O.F.A.	☐
		Cutout dimension (mm): 62 (CONCRETE: 102)	
	15225 0360 B	CONNECTION ST B	☐
		Cutout dimension (mm): 43	
	15225 0360 W	CONNECTION ST W	☐

DELTALIGHT

INFORM R3 DOWN-UP 92748

26823 9220 W-W

Notes: