



COMPO S HP 92720

9 15719 9220 B



AVAILABLE IN

SCHWARZ 9 15719 9220 B

CHROM 9 15719 9220 C

DUNKLES CHROM 9 15719 9220 DC

WEISS 9 15719 9220 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Decke Einbau
CUTOUT SHAPE/SIZE (MM)	rund - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.166
ADJUSTABILITY	0° to 30° schwenkbar, 355° drehbar

Electrical info

CLASS	III
DIM TYPE	Abhängig von der Art der externen Stromversorgung
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9,3W / CRI>90 / 2700K / 880lm
SDCM	SDCM2
RISKGROUP	RG1
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	880lm // 9,3W // 96lm/W
LED TECHNICS (LUMINAIRE)	698lm // 10,7W // 65lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15719_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	System ceiling	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required
	Plasterboard	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required
	Wood	15710 0010 - MOUNTING KIT COMPO S TRIM Required
		15710 0040 - MOUNTING KIT COMPO S TRIMLESS Required

FINISH YOUR SPECIFICATION

LED Netzteil

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4
15710 3400	LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA	1->2
15710 3900	LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA	1
15710 4600	LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA	1
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13
Dimtype: DALI		
15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1->2
Dimtype: DALI		

Mounting Kit

	15710 0010 B MOUNTING KIT COMPO S TRIM B	
Cutout dimension (mm): 55		
	15710 0010 W MOUNTING KIT COMPO S TRIM W	

COMPO S HP 92720

9 15719 9220 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Licht veredelndes Zubehör

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: