



M26L - SPY 391 SOFT 93020 MDL

23437 9020 W

AVAILABLE IN

NOIR 23437 9020 B

ALU BROSSÉ 23437 9020 BRA

ANTHRACITE BROSSÉ 23437 9020 BRAT

CUIVRE BROSSÉ 23437 9020 BRCU

OR BROSSÉ 23437 9020 BRG

BRONZE VIEUX BROSSÉ 23437 9020 BROB

FLEMISH BRONZE 23437 9020 FBR

FLEMISH GOLD 23437 9020 FG

COULEUR OR 23437 9020 GC

NOIR PIANO 23437 9020 PB

BLANC 23437 9020 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 85° inclinable, 360° rotatif
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = dimmable 1 à 10 V ou DALI ou bouton poussoir
ENERGY CLASS	F
CERTIFICATION	EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M26L - SPY 391 SOFT 93020 MDL

23437 9020 W

For detailed installation instructions, please consult the manual : [23437_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

le cable d'alimentation

of Fixtures

 web2print_power_supply_info_box

Min current | Max current



21032 0030

SMART 48 MODULATOR PLUG-IN WD

16


Dimtype: WDL = dimmable sans fil

SMART 48

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 90 011

SMART 48 MODULATOR DIM9

16

Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 012

SMART 48 MODULATOR WD

16


Dimtype: WDL = dimmable sans fil

les alimentations led

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 89 48 100

LED POWER SUPPLY 48V-DC / 100W DIN

8

Dimtype: non dimmable



300 89 48 240

LED POWER SUPPLY 48V-DC / 240W DIN


20

Dimtype: non dimmable

DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL

23437 9020 W



21012 0230


LED POWER SUPPLY 48V-DC / 100W

8

☐

Dimtype: non dimmable

Cutout dimension (mm): 40



21012 0240

LED POWER SUPPLY 48V-DC / 200W


17

☐

Dimtype: non dimmable

Cutout dimension (mm): 40

Terminez votre produit



24144 0010 B

SPY 39 TUBE B

☐

24144 0010 FBR

SPY 39 TUBE FBR

☐

24144 0010 FG

SPY 39 TUBE FG

☐

24144 0010 GC

SPY 39 TUBE GC

☐

24144 0010 W

SPY 39 TUBE W

☐

24144 0070


SPY 39 TUBE SBL

☐

COMPATIBLE COMPOSABLES


SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)

Available Colours



23358 0000

SLM26L - PROFILE



23358 0010


SLM26L - PROFILE 1m




DELTALIGHT

M26L - SPY 391 SOFT 93020 MDL

23437 9020 W



23358 0020 SLM26L - PROFILE 2m



23358 0030 SLM26L - PROFILE 3m



Notes: