



SOLI - FORM 90 93067 Q-DIM

27134 932Q B-B



AVAILABLE IN

BLACK-BLACK 27134 932Q B-B

BLACK-FLEMISH GOLD 27134 932Q B-FG

WHITE-BLACK 27134 932Q W-B

WHITE-WHITE 27134 932Q W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.36 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 16,7W / CRI>90 (R9: 50) / 3000K / 2315lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	2315lm // 16,7W // 138lm/W
LED TECHNICS (LUMINAIRE)	2021lm // 19,2W // 105lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27134_XXXQ_HAND.pdf](#)

SOLI - FORM 90 93067 Q-DIM

27134 932Q B-B

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	5	
63114125 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	13	
1729830 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	5	
2239230 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	11	

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
2319 27111 0020 SOLI - PROFILE 2m	
2319 27111 0030 SOLI - PROFILE 3m	

Notes:

DELTALIGHT

SOLI - FORM 90 93067 Q-DIM

27134 932Q B-B