



## OML50 - INFORM DU TW 984mm 24LED 95063 DIM5

31447 9035 B

AVAILABLE IN  
**BLACK** 31447 9035 B

 [View on website](#)



### General info

|                           |   |
|---------------------------|---|
| <b>LOCATION</b>           | indoor  |
| <b>INGRESS PROTECTION</b> | IP20  |
| <b>WEIGHT (KG)</b>        | 1.7   |
| <b>INFORMATION</b>        | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI DT8)<br>CABLING 1 CIRCUIT |

### Electrical info

|                     |                      |
|---------------------|----------------------|
| <b>ELECTRICAL</b>   | 220-240V / 0 50-60Hz |
| <b>CLASS</b>        | I                    |
| <b>POWER SUPPLY</b> | YES                  |
| <b>DIM TYPE</b>     | DALI                 |
| <b>ENERGY CLASS</b> | E                    |
| <b>CERTIFICATES</b> | EPD, RCM             |

### Lightsource info

|                                    |  |
|------------------------------------|--|
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | DOWN @ 2700K: LED cluster 22,3W / CRI>90 (R9: 50) / 2700K-5000K / 2928lm<br>UP @ 2700K: LED cluster 11,2W / CRI>90 (R9: 50) / 2700K-5000K / 1464lm<br>Or<br>DOWN @ 5000K: LED cluster 20,3W / CRI>90 (R9: 50) / 2700K-5000K / 3504lm<br>UP @ 5000K: LED cluster 10,1W / CRI>90 (R9: 50) / 2700K-5000K / 1752lm |
| <b>SDCM</b>                        | SDCM3  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L80 > 60000  |
| <b>BEAMANGLE</b>                   | 63°  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN @ 2700K: 2928lm // 22,3W // 131lm/W<br>UP @ 2700K: 1464lm // 11,2W // 131lm/W<br>Or<br>DOWN @ 5000K: 3504lm // 20,3W // 173lm/W<br>UP @ 5000K: 1752lm // 10,1W // 173lm/W   |

### Options

WIRELESS CONTROL DIM5

# DELTALIGHT

## **OML50 - INFORM DU TW 984mm 24LED 95063 DIM5**

31447 9035 B

Notes: