DELTALIGHT



OML50 - LED ARRAY DU HE 984mm 940 DIM5

REFERENCE 31040 9405

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
INFORMATION	CLUSTER DOWN: 2898lm/m CLUSTER UP: 2015lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 16,7W / CRI>90 (R9: 50) / 4000K / 2851lm UP: LED cluster 12,2W / CRI>90 (R9: 50) / 4000K / 1982lm
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2851lm // 16,7W // 171lm/W UP: 1982lm // 12,2W // 162lm/W

Options

WIRELESS CONTROL DIM5

Notes: