
DELTALIGHT




DOT.COM ON WALLWASH 12 HO 927

REFERENCE 16315 9200 B

AVAILABLE IN
BLACK 16315 9200 B
WHITE 16315 9200 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 700mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED flex 25,2W / CRI>90 (R9: 60) / 2700K / 3000lm
SDCM	SDCM3
LM80	L70 > 30000
LED TECHNICS (LIGHT SOURCE)	3000lm // 25,2W // 119lm/W
LED TECHNICS (LUMINAIRE)	1738lm // 29W // 60lm/W

Requirements

LED POWER SUPPLY 700mA-DC DIM

For detailed installation instructions, please consult the manual : **16315_XXXX_HAND.pdf**

DOT.COM ON WALLWASH 12 HO 927

16315 9200 B


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

Min current | Max current


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 — 1 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 — 1 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL — 1 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 30



300 48 700 PRO ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM1 — 1 ☐

Dimtype: 1-10V


Cutout dimension (mm): 30



300 48 700 PRO ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 — 1 ☐

Dimtype: DALI


Cutout dimension (mm): 45



300 48 700 PRO WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO WDL — 1 ☐

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 45



300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL — 1 ☐

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 45



300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 — 1 ☐


Dimtype: mains (phase cut-off) or push button

Cutout dimension (mm): 56

DELTALIGHT

DOT.COM ON WALLWASH 12 HO 927


16315 9200 B



300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 2(1)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 82



300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 1(0)


Dimtype: 1-10V or push button

Cutout dimension (mm): 72



300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 1


Dimtype: 1-10V or DALI or push button



300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 1(0)

Dimtype: DALI


Cutout dimension (mm): 72



300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 2(1)

Dimtype: 1-10V or DALI or push button


Cutout dimension (mm): 84



300 90 135 LED POWER SUPPLY MULTI-POWER HV 2

Dimtype: non-dimmable


Cutout dimension (mm): 90



21012 0010 LED POWER SUPPLY MULTI POWER 1

Dimtype: non-dimmable


Cutout dimension (mm): 50



21012 0021 LED POWER SUPPLY MULTI POWER DIM1 1

Dimtype: 1-10V


Cutout dimension (mm): 54



21012 0035 LED POWER SUPPLY MULTI POWER DIM5 1

Dimtype: DALI

Cutout dimension (mm): 54



21012 004W LED POWER SUPPLY MULTI-POWER WDL 2(1)


Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 84

DELTALIGHT

DOT.COM ON WALLWASH 12 HO 927


16315 9200 B



21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL 1

Dimtype: WDL = wireless dimmable


Cutout dimension (mm): 54



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 1

Dimtype: mains (phase cut-off)


Cutout dimension (mm): 55



21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 1

Dimtype: DALI

Cutout dimension (mm): 30



21032 0385 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W PRO DIM5 1

Dimtype: DALI

Cutout dimension (mm): 30

Notes: