





## M26L - SPY 66 TW 96518 DIM5

23292 9015 B

AVAILABLE IN  
**BLACK** 23292 9015 B  
**WHITE** 23292 9015 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 360° rotatable
<b>INFORMATION</b>	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 48V-DC DALI DT8 dimming Optional REFLECTORS 30° & 45° available

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, EPD

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	18°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1087lm // 9W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	776lm // 10,4W // 75lm/W

### Remarks

Take a look at our [MAGNETIC PROFILES](#) movie

### Requirements

SPY 66 TUBE  
 LED POWER SUPPLY 48V-DC

### Accessories

HONEYCOMB 57  
 SPREAD LENS 57  
 LINEAR SPREAD LENS 57  
 SOFTENING LENS 57  
 GLASS SBL 57

# DELTALIGHT

## M26L - SPY 66 TW 96518 DIM5


23292 9015 B

For detailed installation instructions, please consult the manual : [23292\\_XXX5\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

9


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

23

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

9

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

19


Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**24611 0150 B** HONEYCOMB 57 SINGLE USE B




**24611 0160** GLASS SBL 57


# DELTALIGHT

## M26L - SPY 66 TW 96518 DIM5


23292 9015 B




**24611 0170** LINEAR SPREAD LENS 57



**24611 0190** SOFTENING LENS 57




**24611 0200** SPREAD LENS 57



**24611 0210 B** HONEYCOMB 57 DOUBLE USE B

### Finish your product



**24611 0100 B** SPY 66 TUBE B

**24611 0100 FBR** SPY 66 TUBE FBR

**24611 0100 FG** SPY 66 TUBE FG

**24611 0100 GC** SPY 66 TUBE GC

**24611 0100 W** SPY 66 TUBE W

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°

# DELTALIGHT

## M26L - SPY 66 TW 96518 DIM5

23292 9015 B



**24611 0230** SPY 66 REFLECTOR 30°




**24611 0240** SPY 66 REFLECTOR 45°




### COMPATIBLE COMPOSABLES

#### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


#### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m




#### SHIFTLINE M35R profile

#### Available Colours



**23375 0000** SLM35R - PROFILE




**23375 0010** SLM35R - PROFILE 1m




# DELTALIGHT

## M26L - SPY 66 TW 96518 DIM5

23292 9015 B



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: